



PRO SYN 4 Synthetic Blend Multigrade Motor Oil - SAE 5W40

Description

PRO SYN 4 SAE 5W40 is a lubricant on synthetic base, especially designed to answer the highest VW-specifications (VW 505.1) for diesel engines. By using the latest technologies, this engine oil provides an excellent performance on the latest Tdi-engines with pump injector units and a high protection of the exhaust catalyst.

Application

PRO SYN 4 SAE 5W40 was especially developed for the lubrication of Tdi-engines with pump injector units. This oil is also suitable for the most Euro 4 engines of passenger cars.

Quality levels

- API SL/CF
- ACEA A3/B4-04/C3-08
- VW 505.01, 502.00 / 505.00
- Ford WSS-M2C 917-A
- MB 229.31
- BMW LONGLIFE-04
- Porsche
- Renault RN 0700, RN 0710

Photo



Typical properties

Average oil analyses without engagement

Test	Method	Unit	Average result
SAE class			5W40
Density at 15 °C	D4052	Kg/m ³	851
Viscosity at 40 °C	D445	cSt	84.7
Viscosity at 100 °C	D445	cSt	13.9
Viscosity Index	D2270		170
Flash Point COC	D92	°C	235
Pour point	D6892	°C	-39



DENICOL MOTOR OILS N.V. • Kromstraat 54 • 2520 Ranst (Antwerp-Belgium)
 TEL +32 (0)3.485.81.91. - +32.(0)3.485.81.92. • FAX +32 (0)3.485.81.93.
 URL <http://www.denicol.com> • EMAIL denicol@denicol.com