



---

# RACING COMPETITION BRAKE FLUID

High performance – 100 % Synthetic Brake Fluid

---

## *Description*

Racing Competition Brake has been specially formulated for extreme racing conditions where braking systems must operate at very high temperatures.

- Very low pourpoint
- Does not affect seals
- Minimal corrosion

## *Quality level*

SAE J-1703  
FMVSS exceeds 116 DOT 4  
Exceeds DOT 5.1 - DOT 3/4  
ISO 4925

## *Available in*

Cartons of 18x500ml.

## *Application*

To be used under extreme racing conditions where braking systems must operate at very high temperatures. Bleed the system before each race with this fluid to obtain the best results, certainly if the brakes are extremely hot and/or the conditions are humid. Do not mix "Racing Competition Brake Fluid" with other brake fluids in order not to compromise its outstanding performance

## *Photo*



## *Typical properties*

|                                |        |
|--------------------------------|--------|
| Kinematic Viscosity cst - 40°C | 1750   |
| Kinematic Viscosity cst 100°C  | 2.5    |
| Ph                             | 7-11.5 |
| Dry Boiling Point (ERBP)°C     | 312    |
| Wet Boiling point (WERBP)°C    | 205    |

Average oil analysis without engagement

**DENICOL**  
LUBRICANTS

DENICOL MOTOR OILS N.V. • Kromstraat 54 • 2520 Ranst (Antwerp-Belgium)  
TEL +32 (0)3.485.81.91. - +32.(0)3.485.81.92. • FAX +32 (0)3.485.81.93.  
URL <http://www.denicol.com> • EMAIL [denicol@denicol.com](mailto:denicol@denicol.com)