



A1 COMPETITION

High Performance 2-Stroke Oil - Octane Stimulator

Description

A1 Competition is an extra high performance oil for two-stroke engines used in competition, motor-cross, karts, etc, where drivers demand the maximum from their machines under the most extreme conditions.

However, the oil is also perfectly suitable for use in standard two-stroke engines. It is formulated from mineral base oils and special synthetic additives which allow the product to maintain its lubricating properties under the most extreme conditions. This oil is non-premixed and not recommended for use in oil injection systems. Mixture ratio 2,5 % (1/40).

Quality level

API/CEC: TC

Available in

Carton of 24x1 L.
Barrels of 30, 60 and 208 L.

Application

For race, kart, endurance and cross.

Photo



Typical properties

Density 15°C	0.885
Viscosity cst 40°C	208
Viscosity cst 100°C	19.2
Viscosity index	110
Pourpoint °C	-26
Flashpoint COC °C	192

Average oil analysis without engagement

DENICOL
LUBRICANTS

DENICOL MOTOR OILS N.V. ● Kromstraat 54 ● 2520 Ranst (Antwerp-Belgium)
TEL +32 (0)3.485.81.91. - +32.(0)3.485.81.92. ● FAX +32 (0)3.485.81.93.
URL <http://www.denicol.com> ● EMAIL denicol@denicol.com