



OUTBOARD 2-STROKE

2-Stroke Watercraft Oil for Pre-mix & Injection Systems

Description

Outboard 2-Stroke is an ash-less 2-stroke oil of a superior quality, providing maximum performance and lubrication in outboard and other water-cooled 2-stroke engines. Prevents fuel related problems such as combustion chamber deposits, ring sticking and carbon build-up in exhaust systems. Exceeds warranty and service recommendations of the world's leading outboard engine manufacturers, where a NMMA TC-W3 product is specified.

Quality level

NMMA: TC-W3
API/CEC: TD

Available in

Carton of 24x1 L.
Barrels of 30, 60 and 208 L.

Application

For jet ski & outboard engines.

Photo



Typical properties

Density 15°C	0.877
Viscosity cst 40°C	49.1
Viscosity cst 100°C	7.88
Viscosity index	129
Pourpoint °C	-36
Flashpoint COC °C	105

Average oil analysis without engagement



DENICOL MOTOR OILS N.V. • Kromstraat 54 • 2520 Ranst (Antwerp-Belgium)
TEL +32 (0)3.485.81.91. - +32.(0)3.485.81.92. • FAX +32 (0)3.485.81.93.
URL <http://www.denicol.com> • EMAIL denicol@denicol.com