



RACING 4 SYNTEX SAE 10W40 – 5W50 – 15W50

Professional 4-Stroke Oil - Hi-Tech Full Synthetic Engine Oil

Description

Racing 4 Syntex is a highly sophisticated, full synthetic engine oil which meets the latest requirements of modern engine technology.
Assists easy starting and gives excellent oil flow at low temperatures ensuring maximum performance with reduced oil and fuel consumption.
Exceeds the requirements of the world's leading manufacturers of today's Hi-Tech 4-stroke motorcycles.

Quality level

JASO: MA2
API: SG/SJ

Available in

Cartons of 24x1 L, 12x2 L and 6x5 L.
Barrels of 30, 60 and 208 L.

Application

For road & racing engines.
Wet clutch compatible.

Photo



Typical properties

	SAE 10W40	SAE 5W50	SAE 15W50
Density 15°C	0.848	0.854	0.853
Viscosity cst 40°C	91	110	125
Viscosity cst 100°C	14.7	18.5	18.1
Viscosity index	169	189	163
Pourpoint °C	-42	-41	-38
Flashpoint COC °C	230	236	235

Average oil analysis without engagement



DENICOL MOTOR OILS N.V. • Kromstraat 54 • 2520 Ranst (Antwerp-Belgium)
TEL +32 (0)3.485.81.91. - +32.(0)3.485.81.92. • FAX +32 (0)3.485.81.93.
URL <http://www.denicol.com> • EMAIL denicol@denicol.com