



THUMPERLUBE SAE 10W40 – 15W50 – 10W60

High Performance - Professional Motorcycle Oil - Factory Formula Syn-Tech Ester Oil

Description

Thumperlube is a synthetic motor oil of superior quality for hi-tech 4-stroke motorcycle engines, based on synthetic esters and extremely modern additives. The special composition makes it possible to use this oil under the most varied conditions from long idling to full performance and acceleration. Can be used in summer and winter. Wet clutch compatible.



Quality level

JASO MA2
API SL

Available in

Cartons of 24x1 L and 6x5 L.
Barrels of 30, 60 and 208 L.

Application

For motocross, road & racing engines

Photo



Typical properties

	10W40	10W50	15W50	10W60
Density 15 °C	0.876	0.868	0.853	0.861
Viscosity cst 40°C	91	121	124	161
Viscosity cst 100°C	14.2	17.5	18	24.1
Viscosity index	161	160	162	181
Pourpoint °C	-38	-36	-36	-37
Flashpoint COC °C	224	235	260	234

Average oil analysis without engagement



DENICOL MOTOR OILS N.V. • Kromstraat 54 • 2520 Ranst (Antwerp-Belgium)
TEL +32 (0)3.485.81.91. - +32.(0)3.485.81.92. • FAX +32 (0)3.485.81.93.
URL <http://www.denicol.com> • EMAIL denicol@denicol.com